

DA Series

Desktop Barcode Printer

Compact Design Affordable Total Cost of Ownership

The DA Series of direct thermal desktop printers is ideal for a wide variety of applications including product marking, point of sale, retail, small office, shipping labels, and other labeling and tag applications at a very competitive price.

The DA Series is a perfect combination of affordability with a durable and reliable design. The DA series offers both 203 and 300 dpi print resolution with printing speeds up to a fast 6 ips. The large 60-watt power supply produces high-quality printed labels, even at its fastest print speeds.

Key Features

Affordable

The affordable DA210 and DA310 models are priced right and have the features you need for most basic label printing needs using a USB 2.0 or optional Bluetooth interface.

Wireless and Hardware Communications

Need more communications power? The DA220 and DA320 models have more memory and support nearly every major communications option including Serial RS-232, Ethernet, USB, USB host, internal 802.11 a/b/g/n wireless, or internal Bluetooth.

Emulations and More

The DA220 and DA320 models have plenty of memory with 128 MB Flash & 64 MB SDRAM that can be used for easy storage of fonts, international character sets, and graphics. Right out of the box, it supports a fully compatible set of standard industry emulations as well as multiple printer languages, making it easy to replace old installed hardware.

Easy Loading

For easy loading, the DA Series employs a user-friendly double-wall clamshell design with a large 5-inch (outside diameter) center-biased media bay. The spring-loaded label roll holder makes loading simple. Top-of-form sensing by gap, black mark, or notch is standard. The printer also comes with a head-open sensor.

Applications

- Small Parcel Shipping
- Mail Room Address and Routing Labels
- Shipping & Receiving
- Entertainment and Transportation Ticketing
- Retail Point-of-Sale
- File-Folder Labeling
- Specimen Labeling
- Pharmacy Labeling
- Patient Tracking



DA210/DA220 Series – Desktop Direct Thermal Bar Code Printer

Model	DA210	DA310	DA220	DA320
Resolution	8 dots/mm(203 dpi)	12 dots/mm(300 dpi)	8 dots/mm(203 dpi)	12 dots/mm(300 dpi)
Printing Method	Direct Thermal			
Max. Print Speed	152.4mm(6")/second	102mm(4")/second	152.4mm(6")/second	102mm(4")/second
Max. Print Width	108mm(4.25")	105.7mm(4.16")	108mm(4.25")	105.7mm(4.16")
Max. Print Length	2,794mm(110")	1,016mm(40")	25,400mm(1000")	11,430mm (450")
Enclosure	Double-walled plastic			
Physical Dimension	172mm(W)x 165mm(H)x 195mm(D) 6.77"(W)x 6.50"(H)x 7.68"(D)			
Weight	1.5kg(3.31lbs)			
Label Roll Capacity	127mm(5")O.D.			
Processor	32-bit RISC CPU			
Memory	8 MB Flash memory 16 MB DRAM		128 MB Flash memory 64 MB DRAM	
Interface	- USB 2.0(high speed mode) - Internal Bluetooth(factory option)		- PCBA1: USB 2.0 high speed mode, USB Host, RS-232 and Ethernet(standard) - PCBA2: USB 2.0 and Ethernet(factory option) - Internal 802.11 a/b/g/n wireless(factory option) - Internal Bluetooth(factory option)	
Power	External universal switching power supply - Input: AC 100-240V, 2.0A, 50-60Hz - Output: DC 24V, 2.5A, 60W			
Operation Switch, Button, LED	1 power switch, 1 feed button, 1 LED(3 colors: green, amber & red)			
Sensors	- Transmissive gap sensor - Black mark reflective sensor - Head open sensor			
Internal Fonts	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font			
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar(RSS barcode)			
Font and Barcode Rotation	0, 90, 180, 270 degree			
Printer Language	TSPL-EZD(Compatible with EPL, ZPL, ZPL II, DPL)			
Media Type	Continuous, black mark, fan-fold, notched(outside wound)			
Media Width	19mm - 114mm(0.7" - 4.5")			
Media Thickness	0.055mm - 0.19mm(2.16mil - 7.48mil)			
Media Core Diameter	25.4mm - 38mm(1" - 1.5")			
Label Length	10mm - 2,794mm(0.39" - 110")	10mm - 1,016mm(0.39" - 40")	10mm - 25,400mm(0.39" - 1000")	10mm - 11,430mm(0.39" - 450")
Environment Condition	Operation: 5°C to 40°C(41°F to 104°F), 25% - 85% non-condensing Storage: -40°C to 60°C(-40°F to 140°F), 10% - 90% non-condensing			
Safety Regulation	CB, FCC Class A, IC , CE Class A, UKCA, EAC, CCC, BIS, RCM, BSMI, KC, Energy Star 3.2			
Environment Concern	Comply with RoHS, REACH, WEEE, China RoHS			
Accessories	- Quick start guide - USB cable - Power cord - External universal switching power supply			
Limited Warranty	- Printer: 2 years - Printhead: 25km(1 million inches)or 12 months which comes first - Platen: 50km(2 million inches)or 12 months which comes first			
Factory Options	- Internal Bluetooth - Internal MFi Bluetooth		- Real Time Clock - Internal 802.11 a/b/g/n wireless - Internal Bluetooth - Internal MFi Bluetooth - PCBA2: USB2.0 and Ethernet	
Dealer Options	N/A		- Peel-off module - Guillotine cutter(full cut or partial cut) - Linerless with cutter - Linerless with cutter(enhanced) - Linerless with tear	
User Options	1.5" adaptor for 1.5" paper core - External roll mount, media O.D. 214mm(8.4") with 76.2mm(3") core		1.5" adaptor for 1.5" paper core - External roll mount, media O.D. 214mm(8.4") with 76.2mm(3") core - KP-200 Plus keyboard display unit(serial interface)	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 646 3538
 E-mail: emea_sales@tscprinters.com


MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com

ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
 Tel: +91 2249 679 315
 E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com



TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2025 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.
 20250320

www.tscprinters.com

DA220HC/DA320HC Series for Healthcare Specifications

Model	DA220HC	DA320HC
Resolution	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)
Printing Method	Direct Thermal	
Max. Print Speed	152.4mm (6")/second	102mm (4")/second
Max. Print Width	108mm (4.25")	105.7mm (4.16")
Enclosure	• Double-walled plastic • Disinfectant-ready plastic • Antibacterial enclosure	
Physical Dimension	172mm (W) x 165mm (H) x 195mm (D) 6.77" (W) x 6.50" (H) x 7.68" (D)	
Weight	1.5kg (3.31lbs)	
Label Roll Capacity	127mm (5") O.D.	
Processor	32-bit RISC CPU	
Memory	• 128 MB Flash memory • 64 MB DRAM	
Interface	• PCBA1: USB 2.0 high speed mode, USB Host, RS-232 and Ethernet (standard) • PCBA2: USB 2.0 and Ethernet (factory option)	
Power	External universal switching power supply • IEC 60601-1 certified power supply • Input: AC 100-240V, 2.0A, 50-60Hz • Output: DC 24V, 2.5A, 60W	
Operation Switch, Button, LED	1 power switch, 1 feed button, 1 LED (3 colors: green, amber & red)	
Sensors	• Transmissive gap sensor • Black mark reflective sensor • Head open sensor	
Real Time Clock	Standard	
Internal Fonts	• 8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font	
Barcode	• 1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS • 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Font and Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD (Compatible with EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, black mark, fan-fold, notched (outside wound)	
Media Width	19mm - 114mm (0.7" - 4.5")	
Media Thickness	0.055mm - 0.19mm (2.16mil - 7.48mil)	
Media Core Diameter	25.4mm - 38mm (1" - 1.5")	
Label Length	10mm - 25,400mm (0.39" - 1,000")	10mm - 11,430mm (0.39" - 450")
Environment Condition	Operation: 5°C to 40°C (41°F to 104°F), 25% - 85% non-condensing Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class A, IC, CE Class A, UKCA, EAC, CCC, BIS, RCM, BSMI, KC, Energy Star 3.2	
Environment Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	• Quick start guide • USB cable • Power cord • External universal switching power supply	
Limited Warranty	• Printer: 2 years • Printhead: 25km (1 million inches) or 12 months which comes first • Platen: 50km (2 million inches) or 12 months which comes first	
Factory Options	• Internal 802.11 a/b/g/n wireless • Internal Bluetooth • Internal MFi Bluetooth • PCBA2: USB 2.0 and Ethernet	
Dealer Options	• Peel-off module • Guillotine cutter (full cut or partial cut) • Linerless with cutter • Linerless with cutter (enhanced) • Linerless with tear	
User Options	• 1.5" adaptor for 1.5" paper core • External roll mount, media O.D. 214mm (8.4") with 25.4mm (1") core • KP-200 Plus keyboard display unit (serial interface)	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 646 3538
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com


ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
 Tel: +91 2249 679 315
 E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2025 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.
 20250320



www.tscprinters.com