

Alpha-3R

Portable Direct Thermal Printer

Simplify Your Everyday Mobile Printing Needs

Print receipts and tickets on demand and on the go with TSC's Alpha-3R, a cost-effective 3-inch mobile receipt printer. The Alpha-3R is designed for durability, featuring an IP54-rated protective case to resist dust and water. It is comfortable to wear for a full shift without interfering with the user's tasks. The mobile printer is also equipped with many important features and offers a selection of competitive accessories.

Key Features

- IP54-rated environmental case to resist dust and water
- Plastic design with rubber over-mold construction that withstands 1.5m (5 ft) drop
- Wired & wireless communication interfaces: USB 2.0, RS-232, Bluetooth, and 802.11 a/b/g/n
- High capacity 2500mAh rechargeable Li-ion batteries
- Large paper capacity to reduce the frequency of changing paper roll
- High-speed processor and extensive memory for fast print speeds of up to 102mm (4") per second
- Lasts more than 30 hours of printing receipts on a single battery charge
- Supports TSPL-EZ (EPL2 and ZPL emulations), ESC-POS, CPCL emulation
- 2-year standard warranty

Applications

Warehouse & Logistics

• Direct Store Deliveries (DSD)

Retail

- Field Sales/Repairs
- Mobile Point-of-Sale

Transportation

• Onboard Ticketing

Entertainment & Hospitality

Mobile Ticketing

Public Utilities

- Utility Billing/Meter Reading
- Parking Citations



Alpha-3R Accessories

Alpha-3R	Description	User Option
	IP54-Rated Protective Case with Shoulder Strap Add an extra layer of protection for harsh environments with a protective case. While in the case, the printer is IP54-rated for resistance to windblown water and dust. Includes a shoulder strap.	V
	Belt Clip Use the belt clip for a complete hands-free solution.	V
	1-Slot Battery Charger Use the 1-slot charger to quickly charge the battery without any downtime.	V
	4-Slot Battery Charger The 4-slot charger is well-suited for heavy-duty missions.	V
	Li-ion Battery Print receipts for more than 30 hours on a single battery charge.	V
	12-24V DC Vehicle Power Adaptor For automobile vehicle plug to charge on the car.	V
	12-60V DC Vehicle Power Adaptor For automobile vehicle plug to charge on the car.	V
	12-60V DC Vehicle Open End Power Adaptor For charging on the car with open-ended wire.	V

Alpha-3R Specifications

Model	Alpha-3R
Resolution	8 dots/mm(203 dpi)
Printing Method	Direct Thermal
Max. Print Speed	Up to 102mm(4")/second
Max. Print Width	72mm(2.83")
Max. Print Length	2,286mm(90")
Enclosure	Plastic with rubber over-mold construction
Physical Dimension	116mm(W)x148mm(H)x70mm(D) 4.57"(W)x5.83"(H)x2.75"(D)
Weight (Including Battery)	550g(1.212lbs)
Drop Specification	1.5m(5ft)
IP Rating	IP54(with case)
Max. Roll Capacity	Receipt: 57mm(2.25")0D Label: 55mm(2.16")0D
Processor	32-bit RISC CPU
Memory	4 MB Flash memory 8 MB SDRAM
Interface	 USB 2.0 802.11a/b/g/n Wireless (factory option) Bluetooth (factory option) RS-232 (user option)
Power	Two-cell, 7.4V DC, 2500mAh Li-ion rechargeable battery
Operation Switch, Button	3 buttons (On/off, feed, and cover-open) 2 color LED for printer status, 3 LEDs for battery status
Sensors	Reflective sensor Head open sensor
Internal Fonts	8 alpha-numeric bitmap fonts One Monotype Imaging® CG Triumvirate Bold Condensed scalable font
Barcode	 1D barcode Code 39, Code 93, Code 128 UCC, Code 128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 Data bar 2D barcode PDF-417, Maxicode, DataMatrix, QR code, Aztec
Printer Language	TSPL-EZ(EPL2, ZPL2), ESC-POS or CPCL emulation
Media Type	Receipt paper, receipt paper with black mark in printing side & selected label
Media Width	Receipt: 50.8mm - 80mm (2" - 3.15") Label: 50.8mm - 78mm (2" - 3.07")
Media Thickness	Receipt: 0.0508mm - 0.1016mm(2mil - 4mil) Label: Up to 0.14mm(5.5mil)
Media Height	Label: Min. 25.4mm(1")
Environment Condition	Operation: -10°C - 50°C (-14°F - 122°F), 10% - 90% non-condensing Storage: -40°C - 60°C (-40°F - 140°F), 10% - 90% non-condensing
Environmental Concern	Comply with RoHS, WEEE, REACH, China RoHS
Accessories	Quick start guideBelt ClipLi-ion batteryPower adaptor
Limited Warranty	 Printer: 2 years Print head: 25km(1 million inches) or 12 months which comes first Platen: 25km(1 million inches) Battery: 1 year
Factory Options	802.11a/b/g/n Wireless network Bluetooth MFi
User Options	Mini type USB 2.0 USB to RS-232 converter cable Li-ion battery I-slot battery charger I-sl





CORPORATE HEADQUARTERS **TSC Auto ID Technology Co., Ltd.** Tel: +886 2 2218 6789

E-mail: apac_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd. Tel: +886 3 990 6677 E-mail: apac_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc. Tel: +1 657 258 0808 E-mail: americas_sales@tscprinters.com

MEXICO

TSC Mexico Representative Office Tel: +152 (33) 3673 1406 E-mail: americas_sales@tscprinters.com

BRAZIL

TSC Brazil Representative Office Tel: +55 (11) 3554 7225 E-mail: americas_sales@tscprinters.com

TSC Auto ID Technology EMEA GmbH Tel: +49 (0) 8106 37979 000 E-mail: emea_sales@tscprinters.com

TSC Auto ID Technology EMEA GmbH Tel: +7 495 646 3538 E-mail: emea_sales@tscprinters.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE Tel: +971 4 2533 069 E-mail: emea_sales@tscprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd. Tel: +886 2 2218 6789 E-mail: apac_sales@tscprinters.com

TSC India Representative Office Tel: +91 2249 679 315 E-mail: apac_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd. Tel: +86 22 5981 6661 E-mail: apac_sales@tscprinters.com

KOREA

TSC Korea Representative Office Tel: +82 2 852 3322 E-mail: apac_sales@tscprinters.com









