

LINERLESS LABELS



Contact Our Supplies Experts:
info@tscprinters.eu

Our linerless labels in combination with our compatible printers are sustainable, flexible and cost-effective solution available for a wide variety of applications.

Genuine Supplies linerless labels are made up a high sensitivity and heat-resistant direct thermal paper for excellent UV resistance. Rubber based removable adhesive is recommended for grocery stores or quick service restaurants labelling.

These versatile labels are available for mobile, desktop and industrial printers.

Label Comparison Table



TECHNICAL INFORMATION

DOCUMENT	DT Linerless Labels – Permanent		
ITEM NO	38-S080080-1531	Width	80mm / 3.15"
Printer	DA220, DH 220/240	Length	80m
Media core	25mm / 1"	Rolls / box	20
Max OD	100mm / 3.94"	Boxes / pallet	42
Face Material	A white wood free, thermal paper with a temperature sensitive coating with high resistance to humidity, grease, oil, alcohol and so on, for direct thermal printing in black, with high sensitivity. Phenol free, FSC certified.		
	Type:	Thermal top paper	
	Colour and Finish:	White	
	Weight:	72g/sqm	ISO 536
	Thickness:	72µm	ISO 534-80

Adhesive

Rubber based removable adhesive

Reference:	Retail
Type:	Removable, rubber based hot melt
Min. Appl. Temp:	+0°C
Service Temp:	-20°C/+80°C
Peel value Glasses-24h:	0.8 N/25mm FTM2
Tack:	1.2 N FTM9

Applications

- Product Recommendations: for Grocery Stores or quick service restaurants labelling.
- This material has a temperature-sensitive coating for use in a Linerless thermal printers
- Suitable for Direct Thermal Printing
- Adhesive approved by ISEGA (Direct contact dry & moist, non-fatty foodstuffs) according to the German Recommendations XIV. Suitable for food packaging.

Printing Methods

Specific material for direct thermal printing. Testing for suitability between media, printers, inks and varnishes is always recommended prior to use.

Shelf life

9 months, applicable only to the material delivered by TSC which has not undergone further processing, under the following storage conditions:

- This material must be stored as defined by FINAT section 2.5, in temperature 20-25°C and 40-50% Relative Humidity. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life of the product.
- Storage area must be dry and clean. Do not expose to UV/direct sunlight or heat source.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.

