Enterprise Keypad Mobile Computer

EK430 The Ultimate Performance Combination Keypad / Touch Mobile



Specifications

| Performance Characteristics | |
|---|--|
| CPU | Qualcomm Snapdragon SD660 2.2 GHz octa-core |
| Operating System | Android 10; Upgradeable to Android 14 |
| Memory | 4GB RAM / 32GB UFS 4GB RAM / 64GB UFS (Optional) |
| Physical and User Environment Characteristics | |
| Display | 4.3", WVGA, IPS (480 x 800), Corning® Gorilla® Glass |
| Dimensions & Weight | 210 x 76 x 37mm / 450g |
| Touchpanel | Dual input mode with finger, gloved finger and stylus |
| Backlight | LED Backlight |
| Battery | User replaceable Battery 3.6V, 6,800mAh / 3.6V, 7,000mAh(Optional) / Smart Battery / Hot Swap mode support |
| Expansion slot | User accessible MicroSD with 32GB SDHC and up to 512GB SDXC |
| SIM | 1 Nano SIM (Optional) |
| Quick Charging | Fast Charging (Full charge within 5 hours) |
| Interface | USB Type C Connector (USB 3.1), Bottom 8-pin / Rear 10-pin connector |
| Drop spec. | Multiple 6 ft./1.8 m drops to concrete across the operating temperature range per MIL-STD-810G Multiple drops from 2m (6.5ft) per MIL-STD 810G (Wood) at room temperature |
| Tumble spec. | 3000 3.3 ft./1.0m tumbles; meets and exceeds IEC tumble specification |
| Sealing | IP65 |
| Temperature | Operating: -20°C to 50°C / -4°F to 122°F |
| Humidity | 5% to 95% RH (Non-condensing) |
| Keypad & Button | Numeric / Function Numeric (Optional) / Alpha Numeric (Optional) Dual-action side scan triggers |
| Physical and User Environment Characteristics | |
| Communications | LTE (Optional), IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w/mc (Wi-Fi [™] certified IPv4, IPv6, 2x2 MU-MIMO) Class 2, Bluetooth v5.0 with BR / EDR and Bluetooth Low Energy (BLE) Support |
| Camera | Rear: 13MP, LED flash (Optional) / Front: 5MP fixed focus (Optional) |
| Barcode Scanning | 1D & 2D Imager / 1D Laser, Long Range Scanner (Optional) |
| NFC | ISO 14443 Type A and B; FeliCa, and ISO 15693 cards, P2P mode and Card Emulation via Host (HCE) support |
| Accessory | 1SC / 4SC Cradle, 4SC Battery Charger, Trigger Handle, Hand Strap, Holster, Stylus, Protective Film |

Support your Terminal Emulation (TE) apps right out of the box

Expand your options with the TE that is right for you - EK430's TE powered by Wavelink is ready to use at no cost, pre-loaded on every model and pre-licensed on the gun SKU model. Staylinked TE and other licensed TE's are compatible - with support for leading TE's, we truly believe in empowering our users to choose the best solution that fits their ecosystem. Choose the solution that is right for you and transform your green screens to intuitive touch screens to take productivity to a whole new level.



Industry & Applications Warehousing / Distribution

wateriousing / Distributio

- Warehouse management
- Picking and put-away
- Return processing
- Voice-directed applicationsEDI transactions
- Inventory management

Manufacturing

- Inventory management
- Supply-line replenishment
- Safety testing
- Parts tracking

Retail

- Backroom warehouse management
- Store receiving
- Inventory management
- In-store communications

Transportation

- Electronics Toll collection system

BOS[™] Solutions & Software

- BOS[™] Provisioning; Staging; Kiosk; Virtual Key; BOS[™] Keyboard
- BOS[™] VoIP
- BOS[™] PTT, PTT Essential
- BOS[™] Wi-Fine[™] (WiFi analyze application)
- BOS[™] EMM - BOS[™] OTA
- BOS™ OEMConfig

3'rd Party Solutions Integration

- EMM: Airwatch, MobileIron, Mobicontrol, IBM Mass360, XenMobile
- PTT: ESChat, Zello, IMPTT, EveryTalk, AirPTT