

UNCOATED DT LABELS

We understand that your complete satisfaction is based on performance, quality and comprehensive solution support. That's why we offer a wide selection of original consumables that will perfectly match the combination with TSC Auto ID and Printronix Auto ID printers.

With original consumables, you will increase your efficiency, minimize costs and enjoy a printing solution you don't have to worry about.

TECHNICAL INFORMATION

DOCUMENT	LS/23/ 38-T148210-10LF/TSC		
ITEM NO.	38-T148210-10LF		
Type Finishing	Roll		
Winding Direction	Out		
Rolls per Box	6		
Label Width	148 mm	Backing Width	151 mm
Label Length	210 mm	GAP	2,72 mm
Perforation	No	Front Color	No Blanko
Black mark	No	Back Color	No
Back Cut	No	Varnish	No
Core Size	76 mm	Diameter Roll	203 mm (approx.)
Label Across	1	Weight per Box	25 kg (approx.)
Labels per Roll	800		

Product specifications are subject to change without notice.



Premium uncoated paper with permanent acrylic adhesive.

Typical Applications: Shipping / General warehouse / Address / Barcodes / Product ID / Hardware parts supply

Facestock	Base Weight	72 ± 5 g/m ² (ISO 536)
	Caliper	80 ± 5 µm (ISO 534)
	Direct Thermal, white, uncoated, woodfree printing paper with black Imaging thermosensitive coating.	
Adhesive	A general-purpose permanent, acrylic based adhesive	
	Initial Tack	14 N/25mm FTM 9 glass
	Peel Adhesion 90°	8 N/25mm FTM2 st.st.
	Min. Application Temp	5 °C Service Temperature -20 °C to 80 °C
Liner	Basis Weight	51 ± 4 g/ m ² (ISO 536)
	Caliper	50 ± 4 µm (ISO 534)
	A honey glassine paper.	
Laminate	Total Caliper	145 µm±10% ISO 534
Shelf life	One year under recommended storage conditions:	
	<ul style="list-style-type: none"> · Avoid hot, cold or damp conditions. · Store away from heat and direct sunlight. · Store in original packing and keep upright. · Shelf life specified at 20±25°C and 40±50% RH. · Poor storage will reduce the useful life of these labels. 	