

TSC
The Smarter Choice.
GENUINE SUPPLIES

UNCOATED LABELS

Contact Our Supplies Experts:
info@tscprinters.eu

We understand that your complete satisfaction is based on performance, quality and comprehensive solution support. That's why we offer a wide selection of original consumables that will perfectly match the combination with TSC Auto ID and Printronix Auto ID printers.

With original consumables, you will increase your efficiency, minimize costs and enjoy a printing solution you don't have to worry about.

TECHNICAL INFORMATION

DOCUMENT	LS/24/ 38-T040030-14LF/TSC		
ITEM NO.	38-T040030-14LF		
Type Finishing	Roll		
Winding Direction	Out		
Rolls per Box	75		

Label Width	40 mm	Backing Width	43 mm
Label Length	30 mm	Backing Length	33,34 mm

Perforation	No	Front Color	No Blanko
Black mark	No	Back Color	No
Back Cut	No	Varnish	No

Core Size	19 mm	Diameter Roll	55 mm (approx.)
Label Across	1	Weight per Roll	0,10 kg (approx.)
Labels per Roll	450		

Product specifications are subject to change without notice.



TSC PRINTRONIX
AUTO ID

Premium uncoated paper with permanent acrylic adhesive.

Typical Applications: Shipping / General warehouse / Address / Barcodes / Product ID / Hardware parts supply

Facestock	Base Weight	70 g/m ² (ISO 536)
	Caliper	76 µm (ISO 534)
	Direct Thermal, white, uncoated, woodfree printing paper with semi-gloss appearance.	

Adhesive	A general-purpose permanent, acrylic based adhesive		
	Initial Tack	10 N/25mm FTM 9 glass	
	Peel Adhesion 90°	8 N/25mm FTM2 st.st.	
	Min. Application Temp	5 °C Service Temperature -10 °C to 80 °C	

Liner	Basis Weight	58 g/ m ² (ISO 536)
	Caliper	50 µm (ISO 534)
	A brown, supercalendered glassine paper.	

Laminate	Total Caliper	135 µm±15% ISO 534
----------	---------------	--------------------

Shelf life	One year under recommended storage conditions:		
	• Avoid hot, cold or damp conditions.		
	• Store away from heat and direct sunlight.		
	• Store in original packing and keep upright.		
	• Shelf life specified at 20÷25°C and 40÷50% RH.		
	• Poor storage will reduce the useful life of these labels.		