

TSC TH DH Series Rebate

Ends December 31st!

**FUTURE PROOF
YOUR BUSINESS.**
INSTANT REBATE *Save up to \$80*

TH DH Series Key Features

Flexibility

Adapt to evolving business needs and market changes.

Ease of Use

Simplify operations and minimize downtime.

Durability

Invest in a long-lasting solutions.

Act Now! Promotion Period runs

October 1st, 2024, through December 31st, 2024

Region:

Available in United States and Canada

Terms and Conditions:

While supplies last, no back orders, no quantity limitations, only available on select SKU's; ONLY purchases from TSC members with regular price (Special prices do not apply). Promotion only applies to part numbers mentioned. TSC reserves the right to cancel or discontinue the program at any time without prior notice. Contact your salesperson or TSC Territory Manager for further details.

PART NUMBER	MODEL	REBATE
TH220-A001-0001	TH220T	\$40.00
TH220HC-A001-0001	TH220THC	\$40.00
TH320-A001-0001	TH320T	\$40.00
TH320HC-A001-0001	TH320THC	\$40.00
TH240-A001-0001	TH240T	\$65.00
TH240HC-A001-0001	TH240THC	\$65.00
TH340-A001-0001	TH340T	\$80.00
TH340-A001-0001	TH340THC	\$80.00
TH240-A001-0101	TH240TW (Wireless)	\$50.00
TH340-A001-0101	TH340TW (Wireless)	\$65.00
DH220-A001-1001	DH220 (LED)	\$15.00
DH320-A001-1001	DH320 (LED)	\$10.00
DH220-A001-0001	DH220T	\$15.00
DH220HC-A001-0001	DH220THC	\$15.00
DH320-A001-0001	DH320T	\$10.00
DH320HC-A001-0001	DH320THC	\$10.00
DH240-A001-0001	DH240T	\$40.00
DH240HC-A001-0001	DH240THC	\$40.00
DH340-A001-0001	DH340T	\$10.00
DH340HC-A001-0001	DH340THC	\$10.00
DH240-A001-0031	DH240T linerless	\$40.00

TH Series 2-Inch Specifications

Model	TH220T	TH320T
Resolution	8 dots / mm (203 dpi)	12 dots / mm (300 dpi)
Printing Method	Thermal Transfer & Direct Thermal	
Max. Print Speed	203mm(8") / second	152mm(6") / second
Max. Print Width	54mm(2.13")	56.9mm(2.24")
Max. Print Length	25,400mm(1,000")	11,430mm(450")
Enclosure	Clamshell with double-walled plastic	
Physical Dimension	146mm(W) x 179mm(H) x 231mm(D) 5.75"(W) x 7.05"(H) x 9.09"(D)	
Weight	1.8kg(3.97lbs)	
Label Roll Capacity	127mm(5") OD	
Ribbon	90m long, max. OD 37mm, 0.5" core (ink coated outside)	
Ribbon Width	56mm - 58mm (2.20" - 2.28")	
Processor	32-bit RISC CPU	
Memory	128 MB Flash memory 128 MB SDRAM - microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only	
Interface	- USB 2.0 - RS-232 - USB Host - Internal Ethernet, 10/100 Mbps 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module (dealer option) - Bluetooth 5.0 (dealer option) - MFi Bluetooth 5.0 (factory option)	
Power	- External universal switching power supply - Input: AC 100-240V, 1.5A, 50-60Hz - Output: DC 24V, 2.5A, 60W	
Operation Switch, Button, LED/LCD	1 power switch 1 feed button 1 pause button	1 reprint button 3.5" color touch display, 480 x 320 pixel
Sensors	- Transmissive gap sensor - Black mark reflective sensor (position adjustable)	- Ribbon end sensor - Head open sensor
Real Time Clock	Standard	
Internal Font	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font - ARIALUNI.TTF Unicode true type font	
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Font & Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, die-cut, black mark, fan-fold, notch (outside wound)	
Media Width	15mm - 60mm (0.59" - 2.36")	
Media Thickness	0.06mm - 0.19mm (2.36mil - 7.48mil)	
Media Core Diameter	25.4mm - 38.1mm (1" - 1.5")	
Label Length	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")
Environment Condition	- Operation: 0°C to 40°C (32°F to 104°F), 25% - 85% non-condensing - Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class B, IC, cTUVus, NOM, CE Class B, UKCA, EAC, CCC, RCM, BSMI, Energy Star 3.2	
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	- Quick start guide - USB cable - Power cord	- External universal switching power supply 0.5" ribbon paper core
Limited Warranty	- Printer: 2 years - Printhead: 25km (1 million inches) or 12 months which comes first - Platen: 50km (2 million inches) or 12 months which comes first	
Factory Option	MFi Bluetooth 5.0	
Dealer Option	- Peel-off module - Guillotine cutter (full cut and partial cut) - Care label cutter (full cut) 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module - Bluetooth 5.0 module	
User Option	- External label roll mount - KP-200 Plus keyboard display unit 10mm narrow media adaptor	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
Tel: +1 52 (33) 3673 1406
E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
Tel: +55 (11) 3554 7225
E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 000
E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
Tel: +7 495 646 3538
E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tscprinters.com


ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
Tel: +91 2249 679 315
E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
Tel: +82 2 852 3322
E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2024 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.
2024/205



www.tscprinters.com

TH Series 2-Inch for Healthcare Specifications

Model	TH220THC	TH320THC
Resolution	8 dots / mm (203 dpi)	12 dots / mm (300 dpi)
Printing Method	Thermal Transfer & Direct Thermal	
Max. Print Speed	203mm(8") / second	152mm(6") / second
Max. Print Width	54mm(2.13")	56.9mm(2.24")
Max. Print Length	25,400mm(1,000")	11,430mm(450")
Enclosure	- Clamshell with double-walled plastic - Disinfectant-ready plastic, designed with an easy-to-clean surface and a sealed button interface - Antibacterial enclosure	
Physical Dimension	146mm(W) x 179mm(H) x 231mm(D) 5.75"(W) x 7.05"(H) x 9.09"(D)	
Weight	1.8kg(3.97lbs)	
Label Roll Capacity	127mm(5") OD	
Ribbon	90m long, max. OD 37mm, 0.5" core (ink coated outside)	
Ribbon Width	56mm - 58mm (2.20" - 2.28")	
Processor	32-bit RISC CPU	
Memory	128 MB Flash memory 128 MB SDRAM - microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only	
Interface	- USB 2.0 - RS-232 - USB Host - Internal Ethernet, 10/100 Mbps 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module (dealer option) - Bluetooth 5.0 (dealer option) - MFi Bluetooth 5.0 (factory option)	
Power	External universal switching power supply - IEC 60601-1 certified power supply - Input: AC 100-240V, 2.0A, 50-60Hz - Output: DC 24V, 2.5A, 60W	
Operation Switch, Button, LED/LCD	1 power switch 1 feed button 1 pause button 1 reprint button 3.5" color touch display, 480 x 320 pixel	
Sensors	- Transmissive gap sensor - Black mark reflective sensor (position adjustable) - Ribbon end sensor - Head open sensor	
Real Time Clock	Standard	
Internal Font	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font - ARIALUNI.TTF Unicode true type font	
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Font & Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, die-cut, black mark, fan-fold, notch (outside wound)	
Media Width	15mm - 60mm (0.59" - 2.36")	
Media Thickness	0.06mm - 0.19mm (2.36mil - 7.48mil)	
Media Core Diameter	25.4mm - 38.1mm (1" - 1.5")	
Label Length	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")
Environment Condition	- Operation: 0°C to 40°C (32°F to 104°F), 25% - 85% non-condensing - Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class B, IC, cTUVus, CE Class B, UKCA, EAC, CCC, BIS, RCM, Energy Star 3.2	
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	- Quick start guide - USB cable - Power cord - External universal switching power supply 0.5" ribbon paper core	
Limited Warranty	- Printer: 2 years - Printhead: 25km (1 million inches) or 12 months which comes first - Platen: 50km (2 million inches) or 12 months which comes first	
Factory Option	MFi Bluetooth 5.0	
Dealer Option	- Peel-off module - Guillotine cutter (full cut and partial cut) 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module - Bluetooth 5.0 module	
User Option	- External label roll mount - KP-200 Plus keyboard display unit 10mm narrow media adaptor	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 646 3538
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com


ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
 Tel: +91 2249 679 315
 E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2024 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.
 2024I205



www.tscprinters.com

DH Series 2-Inch Specifications

Model	DH220	DH320	DH220T	DH320T
Resolution	8 dots / mm(203 dpi)	12 dots / mm(300 dpi)	8 dots / mm(203 dpi)	12 dots / mm(300 dpi)
Printing Method	Direct Thermal			
Max. Print Speed	203mm(8") / second	152mm(6") / second	203mm(8") / second	152mm(6") / second
Max. Print Width	54mm(2.13")	56.9mm(2.24")	54mm(2.13")	56.9mm(2.24")
Max. Print Length	25,400mm(1,000")	11,430mm(450")	25,400mm(1,000")	11,430mm(450")
Enclosure	Clamshell with double-walled plastic			
Physical Dimension	138mm(W)x172mm(H)x210mm(D) 5.43"(W)x6.77"(H)x8.27"(D)			
Weight	1.6kg(3.53lbs)			
Label Roll Capacity	127mm(5")OD			
Processor	32-bit RISC CPU			
Memory	• 128 MB Flash memory • 128 MB SDRAM • microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only			
Interface	• USB 2.0 • RS-232 • USB Host • Internal Ethernet, 10/100 Mbps • 802.11a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module (dealer option) • Bluetooth 5.0 (dealer option) • MFi Bluetooth 5.0 (factory option)			
Power	External universal switching power supply • Input: AC 100-240V, 1.5A, 50-60Hz • Output: DC 24V, 2.5A, 60W			
Operation Switch, Button, LED/LCD	• 1 power switch • 1 feed button • 1 pause button • 1 reprint button • 1 status indicator • 3 intuitive icon indicators		• 1 power switch • 1 feed button • 1 pause button • 1 reprint button • 3.5" color touch display, 480 x 320 pixel	
Sensors	• Transmissive gap sensor • Black mark reflective sensor (position adjustable) • Head open sensor			
Real Time Clock	Standard			
Internal Font	• 8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font • ARIALUNI.TTF Unicode true type font			
Barcode	• 1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS • 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)			
Font & Barcode Rotation	0, 90, 180, 270 degree			
Printer Language	TSPL-EZD(Compatible to EPL, ZPL, ZPL II, DPL)			
Media Type	Continuous, die-cut, black mark, fan-fold, notch (outside wound), linerless media (for linerless option)			
Media Width	15 - 60mm(0.59" - 2.36")			
Media Thickness	0.06mm - 0.19mm(2.36mil - 7.48mil)			
Media Core Diameter	25.4mm - 38.1mm(1" - 1.5")			
Label Length	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")
Environment Condition	• Operation: 0°C to 40°C(32°F to 104°F), 25% - 85% non-condensing • Storage: -40°C to 60°C(-40°F to 140°F), 10% - 90% non-condensing			
Safety Regulation	CB, FCC Class B, IC , cTÜVus, NOM, CE Class B, UKCA, EAC, CCC, RCM, BSMI, Energy Star 3.2			
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS			
Accessories	• Quick start guide • USB cable		• Power cord • External universal switching power supply	
Limited Warranty	• Printer: 2 years • Printhead: 25km(1 million inches) or 12 months which comes first • Platen: 50km(2 million inches) or 12 months which comes first			
Factory Option	MFi Bluetooth 5.0			
Dealer Option	• Peel-off module • Guillotine cutter (full cut and partial cut) • 802.11a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module		• Bluetooth 5.0 module • Linerless with cutter (full cut) • Linerless with tear	
User Option	• External label roll mount • KP-200 Plus keyboard display unit • 10mm narrow media adaptor			



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
Tel: +1 52 (33) 3673 1406
E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
Tel: +55 (11) 3554 7225
E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 000
E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
Tel: +7 495 646 3538
E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tscprinters.com


ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
Tel: +91 2249 679 315
E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
Tel: +82 2 852 3322
E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2024 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.
2024i205



www.tscprinters.com

DH Series 2-Inch for Healthcare Specifications

Model	DH220THC	DH320THC
Resolution	8 dots / mm (203 dpi)	12 dots / mm (300 dpi)
Printing Method	Direct Thermal	
Max. Print Speed	203mm(8") / second	152mm(6") / second
Max. Print Width	54mm(2.13")	56.9mm(2.24")
Max. Print Length	25,400mm(1,000")	11,430mm(450")
Enclosure	- Clamshell with double-walled plastic - Disinfectant-ready plastic, designed with an easy-to-clean surface and a sealed button interface - Antibacterial enclosure	
Physical Dimension	138mm(W)x 172mm(H)x 210mm(D) 5.43"(W)x 6.77"(H)x 8.27"(D)	
Weight	1.6kg(3.53lbs)	
Label Roll Capacity	127mm(5") OD	
Processor	32-bit RISC CPU	
Memory	128 MB Flash memory 128 MB SDRAM - microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only	
Interface	- USB 2.0 - RS-232 - USB Host - Internal Ethernet, 10/100 Mbps 802.11a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module (dealer option) - Bluetooth 5.0 (dealer option) - MFfi Bluetooth 5.0 (factory option)	
Power	- External universal switching power supply - IEC 60601-1 certified power supply - Input: AC 100-240V, 2.0A, 50-60Hz - Output: DC 24V, 2.5A, 60W	
Operation Switch, Button, LED/LCD	1 power switch 1 feed button 1 pause button 1 reprint button 3.5" color touch display, 480 x 320 pixel	
Sensors	- Transmissive gap sensor - Black mark reflective sensor (position adjustable) - Head open sensor	
Real Time Clock	Standard	
Internal Font	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font - ARIALUNI.TTF Unicode true type font	
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Font & Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, die-cut, black mark, fan-fold, notch (outside wound), linerless media (for linerless option)	
Media Width	15mm - 60mm (0.59" - 2.36")	
Media Thickness	0.06mm - 0.19mm (2.36mil - 7.48mil)	
Media Core Diameter	25.4mm - 38.1mm (1" - 1.5")	
Label Length	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")
Environment Condition	- Operation: 0°C to 40°C (32°F to 104°F), 25% - 85% non-condensing - Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class B, IC, cTUVus, CE Class B, UKCA, EAC, CCC, RCM, Energy Star 3.2	
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	- Quick start guide - USB cable - Power cord - External universal switching power supply	
Limited Warranty	- Printer: 2 years - Printhead: 25km (1 million inches) or 12 months which comes first - Platen: 50km (2 million inches) or 12 months which comes first	
Factory Option	MFfi Bluetooth 5.0	
Dealer Option	- Peel-off module - Guillotine cutter (full cut and partial cut) 802.11a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module - Bluetooth 5.0 module - Linerless with cutter (full cut) - Linerless with tear	
User Option	- External label roll mount - KP-200 Plus keyboard display unit 10mm narrow media adaptor	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 646 3538
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com


ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
 Tel: +91 2249 679 315
 E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2024 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.
 20241205



www.tscprinters.com

TH Series 4-Inch Specifications

Model	TH240T	TH340T
Resolution	8 dots / mm (203 dpi)	12 dots / mm (300 dpi)
Printing Method	Thermal Transfer & Direct Thermal	
Max. Print Speed	203mm (8") / second	152mm (6") / second
Max. Print Width	108mm (4.25")	105.7mm (4.16")
Max. Print Length	25,400mm (1,000")	11,430mm (450")
Enclosure	Clamshell with double-walled plastic	
Physical Dimension	223mm (W) x 186mm (H) x 286mm (D) 8.78" (W) x 7.32" (H) x 11.26" (D)	
Weight	2.8kg (6.17lbs)	
Label Roll Capacity	127mm (5") OD	
Ribbon	300m long, max. OD 67mm, 1" core (ink coated outside) 110m long, max. OD 40mm, 0.5" core (ink coated outside)	
Ribbon Width	40mm - 110mm (1.6" - 4.3")	
Processor	32-bit RISC CPU	
Memory	128 MB Flash memory 128 MB SDRAM - microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only	
Interface	- USB 2.0 - RS-232 - USB Host - Internal Ethernet, 10/100 Mbps	802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module (dealer option) - Bluetooth 5.0 (dealer option) - MFi Bluetooth 5.0 (factory option)
Power	External universal switching power supply - Input: AC 100-240V, 2.0A, 50-60Hz - Output: DC 24V, 3.75A, 90W	
Operation Switch, Button, LED/LCD	1 power switch 1 feed button 1 pause button 1 reprint button 1 status indicator 4 intuitive icon indicators	1 power switch 1 feed button 1 pause button 1 reprint button 3.5" color touch display, 480 x 320 pixel
Sensors	- Transmissive gap sensor - Black mark reflective sensor (position adjustable)	- Ribbon end sensor - Head open sensor
Real Time Clock	Standard	
Internal Font	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font - ARIALUNI.TTF Unicode true type font	
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Font & Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, die-cut, black mark, fan-fold, notch (outside wound)	
Media Width	15mm - 120mm (0.59" - 4.72")	
Media Thickness	0.06mm - 0.19mm (2.36mil - 7.48mil)	
Media Core Diameter	25.4mm - 38.1mm (1" - 1.5")	
Label Length	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")
Environment Condition	- Operation: 0°C to 40°C (32°F to 104°F), 25% - 85% non-condensing - Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class B, IC, cTUVus, NOM, CE Class B, UKCA, EAC, CCC, BIS, RCM, BSMI, KC, Energy Star 3.2	
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	- Quick start guide - USB cable - Power cord - External universal switching power supply	1" ribbon spindle x 2 for 300m ribbon roll 1" ribbon paper core - Media adaptor for 120mm wide media
Limited Warranty	- Printer: 2 years - Printhead: 25km (1 million inches) or 12 months which comes first - Platen: 50km (2 million inches) or 12 months which comes first	
Factory Option	MFi Bluetooth 5.0	
Dealer Option	- Peel-off module - Guillotine cutter (full cut and partial cut) - Care label cutter (full cut)	802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module - Bluetooth 5.0 module
User Option	- External label roll mount - KP-200 Plus keyboard display unit 10mm narrow media adaptor	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
Tel: +1 52 (33) 3673 1406
E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
Tel: +55 (11) 3554 7225
E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 000
E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
Tel: +7 495 646 3538
E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tscprinters.com


ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
Tel: +91 2249 679 315
E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
Tel: +82 2 852 3322
E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2024 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.
2024i205



www.tscprinters.com

TH Series 4-Inch for Healthcare Specifications

Model	TH240THC	TH340THC
Resolution	8 dots / mm (203 dpi)	12 dots / mm (300 dpi)
Printing Method	Thermal Transfer & Direct Thermal	
Max. Print Speed	203mm (8") / second	152mm (6") / second
Max. Print Width	108mm (4.25")	105.7mm (4.16")
Max. Print Length	25,400mm (1,000")	11,430mm (450")
Enclosure	- Clamshell with double-walled plastic - Disinfectant-ready plastic, designed with an easy-to-clean surface and a sealed button interface - Antibacterial enclosure	
Physical Dimension	223mm (W) x 186mm (H) x 286mm (D) 8.78" (W) x 7.32" (H) x 11.26" (D)	
Weight	2.8kg (6.17lbs)	
Label Roll Capacity	127mm (5") OD	
Ribbon	300m long, max. OD 67mm, 1" core (ink coated outside) 110m long, max. OD 40mm, 0.5" core (ink coated outside)	
Ribbon Width	40mm - 110mm (1.6" - 4.3")	
Processor	32-bit RISC CPU	
Memory	128 MB Flash memory 128 MB SDRAM - microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only	
Interface	- USB 2.0 - RS-232 - USB Host - Internal Ethernet, 10/100 Mbps 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module (dealer option) - Bluetooth 5.0 (dealer option) - MFi Bluetooth 5.0 (factory option)	
Power	External universal switching power supply - IEC 60601-1 certified power supply - Input: AC 100-240V, 2.0A, 50-60Hz - Output: DC 24V, 3.75A, 90W	
Operation Switch, Button, LED/LCD	1 power switch 1 feed button 1 pause button 1 reprint button 3.5" color touch display, 480 x 320 pixel	
Sensors	- Transmissive gap sensor - Black mark reflective sensor (position adjustable) - Ribbon end sensor - Head open sensor	
Real Time Clock	Standard	
Internal Font	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font - ARIALUNI.TTF Unicode true type font	
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Font & Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, die-cut, black mark, fan-fold, notch (outside wound)	
Media Width	15mm - 120mm (0.59" - 4.72")	
Media Thickness	0.06mm - 0.19mm (2.36mil - 7.48mil)	
Media Core Diameter	25.4mm - 38.1mm (1" - 1.5")	
Label Length	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")
Environment Condition	- Operation: 0°C to 40°C (32°F to 104°F), 25% - 85% non-condensing - Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class B, IC, cTUVus, CE Class B, UKCA, EAC, CCC, BIS, RCM, KC, Energy Star 3.2	
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	- Quick start guide - USB cable - Power cord - External universal switching power supply 1" ribbon spindle x 2 for 300m ribbon roll 1" ribbon paper core - Media adaptor for 120mm wide media	
Limited Warranty	- Printer: 2 years - Printhead: 25km (1 million inches) or 12 months which comes first - Platen: 50km (2 million inches) or 12 months which comes first	
Factory Option	MFi Bluetooth 5.0	
Dealer Option	- Peel-off module - Guillotine cutter (full cut and partial cut) 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module - Bluetooth 5.0 module	
User Option	- External label roll mount - KP-200 Plus keyboard display unit 10mm narrow media adaptor	



TSC

CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6777
 E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 646 3538
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com


ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
 Tel: +91 2249 679 315
 E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2024 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.
 2024i205



www.tscprinters.com

DH Series 4-Inch Specifications

Model	DH240T	DH340T
Resolution	8 dots / mm(203 dpi)	12 dots / mm(300 dpi)
Printing Method	Direct Thermal	
Max. Print Speed	203mm(8") / second	152mm(6") / second
Max. Print Width	108mm(4.25")	105.7mm(4.16")
Max. Print Length	25,400mm(1,000")	11,430mm(450")
Enclosure	Clamshell with double-walled plastic	
Physical Dimension	208mm(W)x170mm(H)x235mm(D) 8.19"(W)x6.69"(H)x9.25"(D)	
Weight	2.1kg(4.63lbs)	
Label Roll Capacity	127mm(5")OD	
Processor	32-bit RISC CPU	
Memory	128 MB Flash memory 128 MB SDRAM - microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only	
Interface	- USB 2.0 - RS-232 - USB Host - Internal Ethernet, 10/100 Mbps 802.11a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module(dealer option) - Bluetooth 5.0(dealer option) - MFi Bluetooth 5.0(factory option)	
Power	External universal switching power supply • Input: AC 100-240V, 2.0A, 50-60Hz • Output: DC 24V, 3.75A, 90W	
Operation Switch, Button, LED/LCD	1 power switch 1 feed button 1 pause button 1 reprint button 3.5" color touch display, 480 x 320 pixel	
Sensors	- Transmissive gap sensor - Black mark reflective sensor(position adjustable) - Head open sensor	
Real Time Clock	Standard	
Internal Font	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font - ARIALUNI.TTF Unicode true type font	
Barcode	1D barcode Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar(RSS barcode)	
Font & Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD(Compatible to EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, die-cut, black mark, fan-fold, notch(outside wound), linerless media(for linerless option)	
Media Width	15mm - 120mm(0.59" - 4.72")	
Media Thickness	0.06mm - 0.19mm(2.36mil - 7.48mil)	
Media Core Diameter	25.4mm - 38.1mm(1" - 1.5")	
Label Length	5mm - 25,400mm(0.20" - 1,000")	5mm - 11,430mm(0.20" - 450")
Environment Condition	- Operation: 0°C to 40°C(32°F to 104°F), 25% - 85% non-condensing - Storage: -40°C to 60°C(-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class B, IC, cTUVus, NOM, CE Class B, UKCA, EAC, CCC, BIS, RCM, KC, Energy Star 3.2	
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	- Quick start guide - USB cable - Power cord - External universal switching power supply	
Limited Warranty	- Printer: 2 years - Printhead: 25km(1 million inches)or 12 months which comes first - Platen: 50km(2 million inches)or 12 months which comes first	
Factory Option	MFi Bluetooth 5.0	
Dealer Option	- Peel-off module - Guillotine cutter(full cut and partial cut) 802.11a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module - Bluetooth 5.0 module - Linerless with cutter(full cut) - Linerless with tear	
User Option	- External label roll mount - KP-200 Plus keyboard display unit 10mm narrow media adaptor	



CORPORATE HEADQUARTERS
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS
TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 646 3538
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST
TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com

ASIA PACIFIC
TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
TSC India Representative Office
 Tel: +91 2249 679 315
 E-mail: apac_sales@tscprinters.com

CHINA
Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2024 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.
 20241205



www.tscprinters.com

DH Series 4-Inch for Healthcare Specifications

Model	DH240THC	DH340THC
Resolution	8 dots / mm (203 dpi)	12 dots / mm (300 dpi)
Printing Method	Direct Thermal	
Max. Print Speed	203mm (8") / second	152mm (6") / second
Max. Print Width	108mm (4.25")	105.7mm (4.16")
Max. Print Length	25,400mm (1,000")	11,430mm (450")
Enclosure	- Clamshell with double-walled plastic - Disinfectant-ready plastic, designed with an easy-to-clean surface and a sealed button interface - Antibacterial enclosure	
Physical Dimension	208mm (W) x 170mm (H) x 235mm (D) 8.19" (W) x 6.69" (H) x 9.25" (D)	
Weight	2.1kg (4.63lbs)	
Label Roll Capacity	127mm (5") OD	
Processor	32-bit RISC CPU	
Memory	128 MB Flash memory 128 MB SDRAM - microSD card reader for Flash memory expansion, max. 512 GB, FAT32 and exFAT only	
Interface	- USB 2.0 - RS-232 - USB Host - Internal Ethernet, 10/100 Mbps 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module (dealer option) - Bluetooth 5.0 (dealer option) - MFi Bluetooth 5.0 (factory option)	
Power	External universal switching power supply - IEC 60601-1 certified power supply - Input: AC 100-240V, 2.0A, 50-60Hz - Output: DC 24V, 3.75A, 90W	
Operation Switch, Button, LED/LCD	1 power switch 1 feed button 1 pause button 1 reprint button 3.5" color touch display, 480 x 320 pixel	
Sensors	- Transmissive gap sensor - Black mark reflective sensor (position adjustable) - Head open sensor	
Real Time Clock	Standard	
Internal Font	8 alpha-numeric bitmap fonts - Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font - ARIALUNI.TTF Unicode true type font	
Barcode	1D barcode - Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode - TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)	
Font & Barcode Rotation	0, 90, 180, 270 degree	
Printer Language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media Type	Continuous, die-cut, black mark, fan-fold, notch (outside wound), linerless media (for linerless option)	
Media Width	15mm - 120mm (0.59" - 4.72")	
Media Thickness	0.06mm - 0.19mm (2.36mil - 7.48mil)	
Media Core Diameter	25.4mm - 38.1mm (1" - 1.5")	
Label Length	5mm - 25,400mm (0.20" - 1,000")	5mm - 11,430mm (0.20" - 450")
Environment Condition	- Operation: 0°C to 40°C (32°F to 104°F), 25% - 85% non-condensing - Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing	
Safety Regulation	CB, FCC Class B, IC, cTUVus, CE Class B, UKCA, EAC, CCC, BIS, RCM, BSMI, KC, Energy Star 3.2	
Environmental Concern	Comply with RoHS, REACH, WEEE, China RoHS	
Accessories	- Quick start guide - USB cable - Power cord - External universal switching power supply	
Limited Warranty	- Printer: 2 years - Printhead: 25km (1 million inches) or 12 months which comes first - Platen: 50km (2 million inches) or 12 months which comes first	
Factory Option	MFi Bluetooth 5.0	
Dealer Option	- Peel-off module - Guillotine cutter (full cut and partial cut) 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 5.0 combo module - Bluetooth 5.0 module - Linerless with cutter (full cut) - Linerless with tear	
User Option	- External label roll mount - KP-200 Plus keyboard display unit 10mm narrow media adaptor	



TSC

CORPORATE HEADQUARTERS
 TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT
 TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS
 TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO
 TSC Mexico Representative Office
 Tel: +1 52 (33) 3673 1406
 E-mail: americas_sales@tscprinters.com

BRAZIL
 TSC Brazil Representative Office
 Tel: +55 (11) 3554 7225
 E-mail: americas_sales@tscprinters.com

EMEA
 TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 000
 E-mail: emea_sales@tscprinters.com

RUSSIA
 TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 646 3538
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST
 TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com

ASIA PACIFIC
 TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

INDIA
 TSC India Representative Office
 Tel: +91 2249 679 315
 E-mail: apac_sales@tscprinters.com

CHINA
 Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com

KOREA
 TSC Korea Representative Office
 Tel: +82 2 852 3322
 E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2024 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.
 20241205



www.tscprinters.com